

Quick GRIP

Building Envelope Adhesive

Quick GRIP is an industrial-grade aerosolized adhesive in a portable spray system. **Quick GRIP** is formulated to adhere protection courses, drainage composites, insulation, air & vapor barrier membranes, waterproofing membranes, and thru-wall flashings to a variety of substrates. It contains no chlorinated solvents and offers an excellent alternative to methylene chloride-based products.

Quick GRIP provides a fast and economical solution to most building envelope component adhesive requirements.

FEATURES

- ◆ Quick dry time
- ◆ Very long working time
- ◆ Excellent adhesion to a wide variety of substrates
- ◆ Aggressive grab tack
- ◆ Can be used as a primer or an adhesive
- ◆ No clean-up or maintenance

DIRECTIONS FOR USE

1. **Use only after careful consideration of the warnings, directions, and first aid instructions given.**
2. **Surface Preparation:** Surfaces to be bonded should be clean, dry and free of any dust, loose paint, wax, moisture, dirt, grease, oil, rust, or other contaminants.
3. **Adhesive Preparation:** Adhesive should be at 40°F to 100°F. Before initial use, securely attach gun to hose, then hose to canister. Fully open canister valve; do not close until empty.
4. **Working Temperature:** Adhesive must be above 40°F to spray properly.
5. **Adhesive Application:** Spraying from 8 to 12 inches from the substrate, apply a uniform coat of adhesive to one surface, allowing to coat evenly across the substrate. Do not allow adhesive to “puddle”. Use only with approved equipment. Be sure to have sufficient coverage of the surfaces for the application. Do not breathe dust, vapors or spray mist. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone.
6. **Drying:** The adhesive must be allowed to dry before bonding. This will usually take from 1 to 3 minutes at 60°F, under normal conditions. Heat and humidity, or cold weather can cause longer drying times. Daily pretesting is recommended prior to use. Surfaces are dry if adhesive is tacky, but no adhesive transfers to the hand when touched. Complete the bond within 6 hours (under normal conditions) after the adhesive is dry. If the two surfaces don’t grab immediately when brought into contact, they have dried too long.
7. **Assembly:** Position coated surfaces carefully before putting them together since no shifting is possible once contact is made. Bring surfaces together and immediately apply firm pressure over entire surface working from the center to the edges. Apply uniform pressure over 100% of the area to be bonded.
8. **Storage:** After initial assembly, leave the hose and gun attached to canister with the valve open. Detach gun and hose from canister only when transferring to a new canister. Transfer gun and hose to a new canister immediately to keep product from drying in hose. Store out of direct sunlight in a cool, well-ventilated area. Avoid storing container directly on the floor or against an outside wall.
9. Do not use on some membranes and components. When in doubt, conduct compatibility testing on the product to be bonded before use.

ITW TACC

56 Air Station Industrial Park
Rockland, MA 02370

Phone 1-800-503-6991 Fax 1-800-231-8222

info@itwtacc.com

www.itwtacc.com

Quick GRIP

Building Envelope Adhesive

PHYSICAL PROPERTIES

BASE:	Synthetic polymer	SPRAY PATTERN:	Variable web spray
SOLVENT:	Aromatic hydrocarbon	VOC CONTENT:	466.1 grams/liter
FLASH POINT	<0°F (<-18°C)	SHELF LIFE:	1 year, unopened
WEIGHT/GALLON:	6.08 lbs	OPEN TIME:	Up to 6 hours
DRY TIME:	1 – 3 minutes	COLOR:	Clear

NOTE: The shelf life for an unopened container of this adhesive is 1 year from date of manufacture.

ATTENTION: Empty container may still contain pressure and remains hazardous until all flammable vapors, which may explode upon ignition, are gone from residue and container. Observe all labeled hazard precautions. Do not cut, puncture, or weld while hazard exists. Dispose of according to all federal, state, and local regulations.

APPROVED EQUIPMENT

- ◆ SG200 Pro Gun
- ◆ ST9502 Spray Tip
- ◆ MH972 - 6' Hose

**KEEP OUT OF REACH OF CHILDREN
FOR PROFESSIONAL OR INDUSTRIAL USE ONLY
USE ONLY WITH APPROVED EQUIPMENT
SALE TO CONSUMER IS IN VIOLATION OF FEDERAL LAW**

IF YOU CANNOT READ, OR DO NOT UNDERSTAND, ALL DIRECTIONS, CAUTIONS AND WARNINGS, DO NOT USE THIS PRODUCT

SEE MSDS FOR MORE INFORMATION

Notice to Purchaser: NO WARRANTIES, EXPRESS OR IMPLIED ARE MADE INCLUDING MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL ITW TACC, A DIVISION OF ILLINOIS TOOL WORKS INC., OR ITS AFFILIATES ("ITW TACC") BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT INCIDENTAL, OR CONSEQUENTIAL DAMAGES. THE USER MAY SEND A SAMPLE OF PRODUCT TO ITW TACC FOR TESTING. IF SUCH TESTING PROVES A PRODUCT DEFECT, THE USER'S SOLE AND EXCLUSIVE REMEDY IS EITHER REIMBURSEMENT OF THE PURCHASE PRICE OF THE PRODUCT OR REPLACEMENT OF THE CONTAINER OF PRODUCT. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF ITW TACC HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATION OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of a product.

Please direct all inquiries regarding performance of this product to:

ITW TACC

56 Air Station Industrial Park

Rockland, MA 02370

Phone 1-800-503-6991 Fax 1-800-231-8222

info@itwtacc.com www.itwtacc.com

Rev 9/08

