



Single Sided Livestock Waterers



SW1717E

With heat only

SW1717E can be floor or wall mounted



SW2227

Available with or without heat

Features

- Impact resistant polyethylene won't pit, crack or deteriorate like concrete, or rust and corrode like steel
- Poly is FDA and HPB approved, food grade, recyclable plastic
- Rounded, tapered basin won't collect dirt and manure in the corners
- No tools required for easy maintenance
- Quick release stainless steel hatch and service door
- Bolt down locations for easy mounting
- SW1717E comes with stainless steel wall mount bracket and can be floor or wall mounted
- SW2227 available with or without submersible heater
- Non-siphoning to meet "Grade A" dairy requirements
- Insulated with 2"-3.5" thick polyurethane foam

★ To help prevent stray voltage J&D's poly livestock waterers have a ground wire connected to a stainless steel probe that extends into the water. ★

Part#	Description	Capacity	Estimated Maximum Usage*		Drinking Height	Weight
			Dairy	Beef		
Without Heater						
SW2227	Waterer, 22"W x 27"L x 26"H	4.8 Gallons	25	60	19"	40 Lbs
With Heater						
SW1717E	Waterer, 17"W x 17"L x 13.5"H, with 500 Watt Heater	2.9 Gallons	5	10	11"***	26 Lbs
SW2227E	Waterer, 22"W x 27"L x 26"H, with 500 Watt Heater	4.8 Gallons	25	60	19"	40 Lbs
Accessories						
SWP001	Heating Element, Submersible, 250 Watt					
SWP002	Heating Element, Submersible, 500 Watt					
SWP003	Earth Tube, Insulated, 48" x 12.5" OD (Highly recommended for cold climate applications)					
*J&D recommends placing waterers 75' or less from any freestall for livestock convenience.						
**Can be wall mounted to desired height						