



J&D Manufacturing



LEADERS IN MOVING THE WORLD'S AIR

Explosion Proof High Output Deluxe Basket Fan

Explosion proof fans may be required in hazardous areas where gases, vapors, toxic substances or ignitable fibers create a threat of explosion or fire. Examples of these locations include paint spray booths, grain storage dryers, areas with animal gases and many commercial/industrial spaces. The J&D explosion proof fan offers a high velocity air pattern with an energy efficient design and quiet performance.

Features

- **Explosion Proof in:**
Class I Group D
Class II Group F&G
Class I Zone I Group IIA
- OSHA approved guard for installations below and above 7'
- Corrosion resistant powder coated guards
- Optional hot dip galvanized ceiling mount brackets available*
- Explosion Proof, totally enclosed, maintenance free, direct drive high efficiency motors have completely sealed ball bearings, and are covered by a **Full Two Year Warranty**.
- Ships unassembled

OSHA Approved Guard



Part#	Size	HP	Volt	Amps	HZ	Phs	Spd	CCFM	CCFM/Watt	RPM	Drive	Blade	Cord	Color
Single Phase														
VDX24HOB	24"	1/2	115/230	7.4/3.7	60	1	1	7,500	15	1,725	DD	3-Alum	No	Black
VDX30HOB	30"	1/2	115/230	7.4/3.7	60	1	1	9,800	15	1,725	DD	3-Alum	No	Black
3 Phase														
VDX24HOB3	24"	1/2	230/460	2.0/1.0	60	3	1	7,500	15	1,725	DD	3-Alum	No	Black
VDX30HOB3	30"	1/2	230/460	2.0/1.0	60	3	1	9,800	15	1,725	DD	3-Alum	No	Black

DD-Direct Drive

*Fan does not come with bracket. See below for recommended bracket.

Recommended Brackets

Part#	Fan Size	Description	Finish
VRSBR5-HDG	24"	Standard Bolt On Flag Mount Ceiling Bracket	Hot Dip Galvanized
VRSBR6-HDG	30"	Standard Bolt On Flag Mount Ceiling Bracket	Hot Dip Galvanized

VRSBR5-HDG
VRSBR6-HDG

