



# J&D Manufacturing



LEADERS IN MOVING THE WORLD'S AIR

## Aluminum Intake Power Shutter

Aluminum Power Shutters from J&D are designed to be used as an inlet to bring fresh air into your building, and may also be used for free-air exhaust. All Power Shutters include a shutter motor kit and heavy duty aluminum extrusion frame with welded corners for extra strength. Order without a cord, or choose our pre-wired models with a 9' 115 volt cord for "No Electrician Required" operation.

### Features

- Includes shutter motor kit and hardware
- High efficiency shutter with tie bar to eliminate shutter flapping
- Nylon bearings and solid shafts for smooth performance
- Heavy duty aluminum extrusion frame
- Corners are precision milled and welded for durability
- Interlocking louvers for maximum weather seal
- Double panel models include additional center bar for extra strength



### Power Shutter Pre-wired With 9' Cord

Part#	Size	Panel	Rough Opening	Pre-wired for
VRSG12A-PSC	12" x 12"	Single	12.5" x 12.5"	115 Volts
VRSG16A-PSC	16" x 16"	Single	16.5" x 16.5"	115 Volts
VRSG18A-PSC	18" x 18"	Single	18.5" x 18.5"	115 Volts
VRSG20A-PSC	20" x 20"	Single	20.5" x 20.5"	115 Volts
VRSG24A-PSC	24" x 24"	Single	24.5" x 24.5"	115 Volts
VRSG30A-PSC	30" x 30"	Single	30.5" x 30.5"	115 Volts
VRSG36A-PSC	36" x 36"	Double	36.5" x 36.5"	115 Volts
VRSG40A-PSC	40" x 40"	Double	40.5" x 40.5"	115 Volts
VRSG42A-PSC	42" x 42"	Double	42.5" x 42.5"	115 Volts
VRSG48A-PSC	48" x 48"	Double	48.5" x 48.5"	115 Volts
VRSG54A-PSC	54" x 54"	Double	54.5" x 54.5"	115 Volts
VRSG60A-PSC	60" x 60"	Double	60.5" x 60.5"	115 Volts
<b>Optional Temperature Control</b>				
VC115-C	Single Stage Thermostat with 8' Piggyback Cord			

### Power Shutter Without Cord

Part#	Size	Panel	Rough Opening	Shutter Motor
VRSG12A-PS	12" x 12"	Single	12.5" x 12.5"	115/230 Volts
VRSG16A-PS	16" x 16"	Single	16.5" x 16.5"	115/230 Volts
VRSG18A-PS	18" x 18"	Single	18.5" x 18.5"	115/230 Volts
VRSG20A-PS	20" x 20"	Single	20.5" x 20.5"	115/230 Volts
VRSG24A-PS	24" x 24"	Single	24.5" x 24.5"	115/230 Volts
VRSG30A-PS	30" x 30"	Single	30.5" x 30.5"	115/230 Volts
VRSG36A-PS	36" x 36"	Double	36.5" x 36.5"	115/230 Volts
VRSG40A-PS	40" x 40"	Double	40.5" x 40.5"	115/230 Volts
VRSG42A-PS	42" x 42"	Double	42.5" x 42.5"	115/230 Volts
VRSG48A-PS	48" x 48"	Double	48.5" x 48.5"	115/230 Volts
VRSG54A-PS	54" x 54"	Double	54.5" x 54.5"	115/230 Volts
VRSG60A-PS	60" x 60"	Double	60.5" x 60.5"	115/230 Volts
<b>Optional Temperature Control</b>				
VC115	Single Stage Thermostat without Cord			

### Power Shutter Pre-wired With 9' Cord

For "No Electrician Required" operation, choose our Aluminum Power Shutters pre-wired for 115 volts with a 9' cord. Combine with our VC115-C single stage thermostat to automatically open and close your shutter at the temperature set point. Simply plug the thermostat into your wall outlet, then plug your Power Shutter into the thermostat for instant operation.

### Shutter Motors and Shutter Motor Kits

Part#	Description
<b>Shutter Motors</b>	
VRSM10	Motor, 115/230V
VRSM10-C	Motor, Wired for 115V, with 9' Cord
VRSM10-WR	Motor, 115/230V, with Water Resistant Junction Box
<b>Shutter Motor Kits (Motor &amp; Hardware) for 12"-60" Shutters</b>	
VRS1260	Kit, 115/230V
VRS1260-C	Kit, Wired for 115V, with 9' Cord
VRS1260-WR	Kit, 115/230V, with Water Resistant Junction Box

### 1 Year Warranty on Shutter Motor



#### Shutter Motor Kits Include:

- Motor
- Lever arm
- Chain
- S-Hooks
- Tension Springs
- Mounting Bracket
- Assembly Hardware