



J&D Manufacturing



Livestock Waterers



SW2384



SW23115



SW23144

**Order with
or without
heat**

Features

- Impact resistant polyethylene won't pit, crack or deteriorate like concrete, or rust and corrode like steel
- Poly is FDA and HPB approved, food grade, recyclable plastic
- Float and valve are in the center of the unit, leaving the full trough open for livestock accessibility
- Rounded, tapered basin won't collect dirt and manure in the corners
- Large drain plug in the center to rapidly drain water in 20 - 40 seconds
- No tools required for easy maintenance
- Quick release stainless steel hatch and service door
- Bolt down locations for easy mounting
- Submersible heater available (must order separately)
- Non-siphoning to meet "Grade A" dairy requirements
- Insulated with 2"-3.5" thick polyurethane foam

★ **To help prevent stray voltage J&D's poly livestock waterers have a ground wire connected to a stainless steel probe that extends into the water.** ★

Part#	Description	Size	Capacity	Estimated Maximum Usage*		Drinking Height	Weight
				Dairy	Beef		
SW2384	Waterer, 23.5"W x 84"L x 24"H	(7')	35 Gallons	125	250	24"	150 Lbs
SW23115	Waterer, 23.5"W x 115"L x 24"H	(10')	59 Gallons	210	420	24"	185 Lbs
SW23144	Waterer, 23.5"W x 144"L x 24"H	(12')	70 Gallons	250	500	24"	260 Lbs
Accessories							
SWP001	Heating Element, Submersible, 250 Watt						
SWP002	Heating Element, Submersible, 500 Watt						
SWP003	Earth Tube, Insulated, 48" x 12.5" OD (Highly recommended for cold climate applications)						

*J&D recommends placing waterers 75' or less from any freestall for livestock convenience.