



J&D Manufacturing



LEADERS IN MOVING THE WORLD'S AIR

Pruden Inlet Actuator

J&D Manufacturing's Pruden Inlet Actuators are designed to work with Pruden Actuated Ceiling Inlets and Cool Slider Wall Inlets. Our Inlet Actuator has a protective housing with sealed electrical components for maximum performance and long life under the harshest agricultural conditions. The adjustable mounting brackets and quick-connect plug in sockets make the Pruden Inlet Actuator a snap to install. Use with the J&D Switching Center for automatic inlet control.

Features

- Designed to work with all types of inlet openings including ceiling, wall, slider or curtain (verify load capacity)
- All parts protected against the harshest corrosive agricultural elements including hogs
- Thermal overload protection
- Potentiometer and electrical components are sealed and protected from water and humidity
- Quick and easy to connect with plug in sockets
- Keyed shaft to prevent shaft from turning
- 1,000 lbs startup and 800 lbs dynamic load
- 24" stroke with a speed of 10" per minute
- Includes two adjustable mounting brackets
- Can be mounted to ceiling or sidewalls
- **One Year Warranty**



Switching Centers

Features

- Available with or without relay
- Units can be wired for either 115 or 230 volts



PFISC



PFISC-R

Part #	Volts	Hz	Description
Actuators			
PFACT115-24	115	50/60	Linear Actuator, 24" Stroke Travel with a Speed of 10" per Minute, with Mounting Brackets
PFACT230-24	230	50/60	Linear Actuator, 24" Stroke Travel with a Speed of 10" per Minute, with Mounting Brackets
Switching Centers			
PFISC	115/230		Switching Center
PFISC-R	115/230		Switching Center with Relay

Contact J&D Manufacturing to determine actuator requirements per number of inlets.