



Double Sided Livestock Waterers



SW2128



SW2232

Available with or without heat

Features

- Impact resistant polyethylene won't pit, crack or deteriorate like concrete, or rust and corrode like steel
- Poly is FDA and HPB approved, food grade, recyclable plastic
- Rounded, tapered basin won't collect dirt and manure in the corners
- Requires no tools for easy maintenance
- Quick release stainless steel hatch and service door on SW2232 series
- Quick release black poly hatch and service door on SW2128 series
- Bolt down locations for easy mounting
- Available with or without submersible heater
- Non-siphoning to meet "Grade A" dairy requirements
- Insulated with 2"-3.5" thick polyurethane foam

★ **To help prevent stray voltage J&D's poly livestock waterers have a ground wire connected to a stainless steel probe that extends into the water.** ★

Part#	Description	Capacity	Estimated Maximum Usage *			Drinking Height	Weight
			Dairy	Beef	Hog		
Without Heater							
SW2128	Waterer, 21.75"W x 28"L x 16"H	5.3 Gallons	25	60	65	12"	32 Lbs
SW2232	Waterer, 22"W x 32"L x 26"H	9.2 Gallons	50	100		19"	54 Lbs
With Heater							
SW2128E	Waterer, 21.75"W x 28"L x 16"H, with 500 Watt Heater	5.3 Gallons	25	60	65	12"	32 Lbs
SW2232E	Waterer, 22"W x 32"L x 26"H, with 500 Watt Heater	9.2 Gallons	50	100		19"	54 Lbs
Accessories							
SWP001	Heating Element, Submersible, 250 Watt						
SWP002	Heating Element, Submersible, 500 Watt						
SWP003	Earth Tube, Insulated, 48" x 12.5" OD (Highly recommended for cold climate applications)						

*J&D recommends placing waterers 75' or less from any freestall for livestock convenience.